



innovation streamlined with versatility in mind

innovation & inspiration

ignature

innovation streamlined with versatility in mind





innovation streamlined with versatility in mind



product construction varn/fibre pile weight pile height gauge tile size total thickness

carton size total weight

dimensional stability backing

pixel, static multi-level loop solution dyed nylon 646g/m²

4mm 1/10 500mm x 500mm 7.0mm (Thermo Bak™) 9.5mm (Comfi Bak®)

5m²5.0kg/m² (Thermo Bak™) 4.2kg/m² (Comfi Bak®)

< 0.15% Thermo Bak™, Comfi Bak®

electrostatic propensity fire rating ISO 9239.1

recommended adhesive installation method

Comfi Bak® option shapes option

availability

6.5 kw/m² critical radiant flux (Thermo Bak™) 9.0 kw/m² critical radiant flux (Comfi Bak®) RLA Polymers GS300 quarter turn, directional, ashlar, brick

50m² minimum 50m² minimum

in stock

Traffic















numerical 1417




algorithm 8948



statistic 0099



balance 9975



fragment 9800



squared 1675



particle 1007



ingot 1700



fraction 0775



compute 1799



Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification. 06/2018©