

## Specification Data Sheet

### Pronto Engineered Oak, Wide Plank - 190 x 14/3 mm & Herringbone Parquetry - 120 x 600 x 14/3mm.

**Pronto Oak** features a **Hi-Spec A/B/C visual grade** wear layer providing a cleaner, sharper look. The product is manufactured with Tongue & Groove profile that assists with pattern alignment and ease of installation. With a tight palette of pre-finished colours that includes natural oak along with light to darker tones, Pronto Oak is ready to deliver an eye-catching impact for your next project.

Pronto planks & herringbone parquetry are manufactured with a **3mm** solid European Oak wear layer permanently bonded onto a **11mm** mixed hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of **14mm**. Perfectly suited for residential, multi-residential and commercial applications. **Interior use only.**

**Key Features;** Engineered to exacting standards. Manufactured from sustained yield forest resources, visual décor delivers a clean sharper look with less knots. Wear layer can be re-sanded and rejuvenated throughout the products lifecycle.

**Colour Range;** Natural oak with a light to darker palette.

**Description;** Engineered European Oak, Tongue & Groove profile. **Herringbone Parquetry direct adhesive fix only.**

**Grade & Surface;** A/B/C **Hi Spec. grade**, may contain small knots, sapwood and natural characteristics that are filled and patched to compliment surface colour and feature. Pre-finished Matte, PU lacquer coating. Light wire brushed surface.

**Size & Length;** **Plank**, 190mm width, 14/3mm thickness, 1900mm length, inc. nested shorts. **Quantity;** 2.166m<sup>2</sup> / Ctn., 50 Ctns / pallet. **Herringbone Parquetry**, 120mm width, 14/3mm thickness, 3mm wear layer, 600mm length. **Quantity;** 0.864m<sup>2</sup> / Ctn., 120 Ctns / pallet.

**Profile;** Tongue & Groove (T&G), Micro Bevelled Edges.

**Acoustic outcome;** Plank Test Result on 2mm Underlay L'nT,w 45. **Parquetry requires direct trowel adhesive install, cannot be floated.**

**Fire Test Data;** AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, 3.5kW/m<sup>2</sup>. Mean Smoke Development, 26 percent minutes.

**Slip Resistance;** In accordance with AS/NZS 4586; 2013 **P3**. **VOC Emissions;** E1, (Below World Health Organisation Levels).

**R-Value Thermal Resistance;** 0.0875. **JANKA Hardness;** 5.5 – 6.0kN.

**Accessories;** Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

**Pre-finished, quick, and easy to lay - no dust, no smell, and no mess.** Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, [info@preferencefloors.com.au](mailto:info@preferencefloors.com.au) or a local sales office.

[www.preferencefloors.com.au](http://www.preferencefloors.com.au)

#### Adelaide (SA)

t +61 8 8262 2774  
sa@preferencefloors.com.au

#### Brisbane (QLD)

t +61 7 3875 1688  
qld@preferencefloors.com.au

#### Melbourne (VIC)

t +61 3 9794 5111  
vic@preferencefloors.com.au

#### Perth (WA)

t +61 8 9471 7785  
wa@preferencefloors.com.au

#### Sydney (NSW)

t +61 2 9738 1188  
sales@preferencefloors.com.au