

## Specification Data Sheet

### De Marque Oak Parquetry Collection, Herringbone - 120 x 600 x 21/6mm & Chevron – 90 x 600 x 21/6mm.

The stunning De Marque engineered Oak Herringbone & Chevron parquetry collection is available with a universal Tongue & Groove profile that assists with pattern alignment and ease of installation. With a contemporary palette of pre-finished colours, the range will provide wonderful warmth and charm to almost any interior.

The parquetry planks are manufactured with a 6mm solid European Oak wear layer permanently bonded onto a 15mm mixed hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of 21mm. Perfectly suited for residential, multi-residential and commercial applications. **Interior use only.**

**Key Features;** Engineered to exacting standards. Manufactured from sustained yield forest resources, extremely stable with excellent wear resistance. Wear layer can be re-sanded and rejuvenated throughout the products lifecycle.

**Colour Range;** Natural oak, light Scandinavian tones, along with warm traditional parquetry colours. **Raw** (un-coated) available for site specific stain & finishing. Custom colours for large commercial projects by arrangement, minimum volume requirements apply.

**Description;** Engineered European Oak, Tongue & Groove profile for **direct trowel adhesive installation only.**

**Grade & Surface;** A/B/C grade, may contain small knots, sapwood and natural characteristics that are filled and patched to compliment surface colour and feature. Pre-finished Matte, PU lacquer coating. Light wire brushed surface.

**Size & Length;** Herringbone, 120mm width, 21mm thickness, 6mm wear layer, 600mm length. **Quantity;** 0.576m<sup>2</sup> / Ctn., 88 Ctns / pallet. Chevron, 90mm width, 21mm thickness, 6mm wear layer, 600mm length. **Quantity;** 0.432 / Ctn, 132 Ctns, / pallet.

**Profile;** Tongue & Groove (T&G), Micro Bevelled Edges.

**Acoustic outcome;** Test Result L'nT,w 45 (indicative). **Direct trowel adhesive installation only, cannot be floated.**

**Fire Test Data;** AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, 5.5kW/m<sup>2</sup>. Mean Smoke Development, 6 percent minutes.

**Slip Resistance;** In accordance with AS/NZS 4586; 2013 P3. **VOC Emissions;** E1, (Below World Health Organisation Levels).

**R-Value Thermal Resistance;** 0.13125. **JANKA Hardness;** 5.5 – 6.0kN.

**Accessories;** Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

**Pre-finished, quick, and easy to lay - no dust, no smell, and no mess.** Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, [info@preferencefloors.com.au](mailto:info@preferencefloors.com.au) or a local sales office.

[www.preferencefloors.com.au](http://www.preferencefloors.com.au)

#### Adelaide (SA)

t +61 8 8262 2774  
sa@preferencefloors.com.au

#### Brisbane (QLD)

t +61 7 3875 1688  
qld@preferencefloors.com.au

#### Melbourne (VIC)

t +61 3 9794 5111  
vic@preferencefloors.com.au

#### Perth (WA)

t +61 8 9471 7785  
wa@preferencefloors.com.au

#### Sydney (NSW)

t +61 2 9738 1188  
sales@preferencefloors.com.au