

Specification Data Sheet

OAKLEAF HD PLUS 48hr Water- Resistant 8mm & 12mm Laminate Click flooring for floating install only.

OAKLEAF HD PLUS laminate flooring delivers amazing realism with décor visuals so natural you would think you were looking at a natural timber plank. Using the latest digital imaging technology, a stunning range has been created that showcases popular Australian Timber species along with Oak & Hickory décors. Featuring a 48hr moisture protected treatment for the micro bevel edges with up to 30 pattern repeats, these planks deliver all the natural charm & character you would expect from a natural timber floor. OAKLEAF HD PLUS also features a 48hr independently tested Water-Resistant core providing ultimate peace of mind for when little accidents occur.

OAKLEAF HD PLUS laminate is AC4 rated, making it tough enough for everyday living and ideally suited for the wear and tear associated with modern family environments. OAKLEAF HD PLUS laminate is dimensionally stable, exceptionally durable and offers great visual appeal for residential décors, and commercial fit-out.

Key Features; Engineered to exacting standards. Manufactured from sustainable wood fibre forest resources. Extremely stable with excellent AC4 wear resistance.

Colour Range; 14 Colour decors for 12mm & 8 Colour decors for 8 mm, including Blackbutt & Spotted Gum.

Description; Laminate with a patented click profile for floating installation.

Grade & Surface; 12mm- & 8mm AC4 surface for high scratch resistant performance. Matte coating, registered embossed surface.

Size & Length; 12mm – 2200 x 196mm Quantity; 1.725m² / carton. 8mm - 1215 x 195mm Quantity; 1.895m² / carton

Profile; Valinge 5g Angle/Click profile. Micro Bevelled Edges.

Acoustic outcome; Test Result with 2mm Green Underlay, 12mm - L'nT,w 45 & 8mm - L'nT,w 44.

Fire Test Data; AS/ISO9239.1-2003, 12mm CHF, 4.4 kW/m² & MSD, 12% minutes. 8mm CHF, 5.4kW/m² & MSD, 9% minutes.

Slip Resistance; In accordance with AS/NZS 4586; 2013 P3. **VOC Emissions;** E1, (Below World Health Organisation Levels).

Swell Testing; Conforms to EN 13329:2016 + A1:2017 & ISO 24336:2005 & NALFA, T Seam - Swell & Seepage Test >80hrs.

R-Value Thermal Resistance EN 12996:2001; 12mm - 0.0730 & 8mm - 0.0520

Accessories; Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

Pre-finished, quick, and easy to lay - no dust, no smell, and no mess. Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, info@preferencefloors.com.au or a local sales office.

www.preferencefloors.com.au

Adelaide (SA)

t +61 8 8262 2774
sa@preferencefloors.com.au

Brisbane (QLD)

t +61 7 3875 1688
qld@preferencefloors.com.au

Melbourne (VIC)

t +61 3 9794 5111
vic@preferencefloors.com.au

Perth (WA)

t +61 8 9471 7785
wa@preferencefloors.com.au

Sydney (NSW)

t +61 2 9738 1188
sales@preferencefloors.com.au