

intelli**planks**
dynamic 



intelligent technology
combined with smart benefits

innovation & inspiration

|  [®]
Signature
floorconcepts

for total flexibility & cost efficiency



blast 100 **burst 200**
burst 200CB **crush 300** **demolish 400** **detonate 500** **explode 600**
explode 600CB **shatter 700** **smash 800**

product construction
yarn/fibre
pile weight
pile height
gauge
tile size
total thickness

carton size
total weight

dimensional stability
backing
electrostatic propensity
fire rating ISO 9239.1
recommended adhesive

dynamic, dynamic CB
multi-level loop
solution dyed nylon
646g/m² (19oz)
4mm
1/12
250mm x 1000mm
Thermo Bak™ 6.5mm
Comfi Bak® 9.5mm
5m²
Thermo Bak™ 5.0kg/m²
Comfi Bak® 4.2kg/m²
<0.15%
Thermo Bak™, Comfi Bak®
<2.0kv
> 4.5 kw/m² critical radiant flux
RLA Polymers GS300

installation method
Comfi Bak® option

customise Shapes®
traffic
warranty
fire
stain/soil
sustainability

availability

ashlar, herringbone, basket weave
50m² minimum
(non-stocked colours only)
50m² minimum
extra heavy duty commercial
15 year
suitable all areas
Ultra Gard
GreenTag® Green Rate Level A
EPDs and Declare labels
WELL & LBC eligible
Thermo Bak™ in stock in all
colours, Comfi Bak® in stock
in two colours



Traffic
Extra Heavy Duty Commercial

Warranty
15 Year Limited

Fire
Suitable All Areas

Stain/Soil
Ultragard



au 03 9401 0888
nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz

Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification. 08/2022©